



# Heavy Duty Color Backup Camera System With 5" LCD Monitor & Two Camera Inputs for Work Trucks, Vans, Buses, RVs & Trailers



KIT P/N: STSK5465

- Rugged High Resolution 5" LCD Color Monitor With Ultra Sharp Display
- System Can Accept Up to 2 Camera Inputs for Multiple Camera Views
- Weatherproof Heavy Duty Camera Provides 120° Field Of Vision
- 18 Infrared LEDs in Camera Provide Up To 30 Ft. of Night Time Visibility
- Modern Illuminated Membrane Control Panel
- Built-In Camera Microphone & Powerful Monitor Speakers
- Versatile Mounting On Dashboard or Overhead Location
- One Year Warranty Included



### MONITOR P/N: STSM208 (Included In Kit)

Screen Size (Diagonal)	5"
Maximum No. of Cameras	2 Inputs/Channels
Screen Ratio	16:9
Contrast Ratio	500:1
Video System	NTSC
Voltage Input	12 ~ 32 Vdc
Operating Temperature °F (C°)	5° to 149° (-15° to +65°)
Storage Temperature °F (C°)	-4° to 158° (-20° to +70°)
Vibration Rating	6.9G @ 10-30Hz, 3mm Amplitude
Speaker Impedance	8 Ohms
Weight	0.7 lb.
Dimensions W x H x D	5.5" x 4" x 1.1"
Other Features	Auto dimming backlit buttons
Mounting Brackets	Standard Duckfoot, Optional U-Bracket & AMPs Mount



**STSU1004**

Optional U-Bracket

### CAMERA P/N: STSC141 (Included In Kit)

Image Device	Sony 1/4" CCD
Pixels	270,000
TV Lines	420
InfraRed LED's	18 High-Output
Minimum Illumination	0 LUX (Infrared LED's on)
Night Vision Range	30 Feet
Video Output	1.0 Vp-p, 75 Ohm
Dust/Water Rating	IP69k
Shock Rating	100G
Vibration Rating	15G
Field of View	120°
Operating Temperature °F (°C)	-15° to 160° (-25° to +70°)
Storage Temperature °F (°C)	-20° to 176° (-30° to +80°)
Weight	.6 lb.
Dimensions W x H x D	3" x 2" x 2"



**STSC141**

Standard Camera

#### Optional Cameras:



**STSC106**

Wide Angle  
Bullet Camera



**STSC109B**

Universal L/R  
Side Camera



**STSC112**

License Plate Camera

### HARNESS P/N: STSH341 (Included In Kit)

65' Heavy Duty w/ Twist - Lock Connectors

#### Optional Harnesses:

- STSH303 - 33' Harness
- STSH304 - 16.5' Harness Extension
- STSH394 - Heavy Duty Coilcord  
Quick Disconnect Kit  
w/ 16.5' Harness



**STSH341**

Standard Harness

#### Optional Harnesses:



**STSH303**



**STSH304**



**STSH394**